

DEENDAYAL PORT AUTHORITY**TD Division**

Sub :- Quotation for "Providing and Fixing Barbed Wire Fencing alongside Westside of A.O. Building Boundary Wall -Government Office area."

SCHEDULE-B

Sr. No.	Description of Items	Qty.	Rate		Unit	Amount
			in fig	in words		
1	Excavating holes more than 0.10 cum & upto 0.5 cum including getting out the excavated soil, then returning the soil as required in layers not exceeding 20cm in depth, including consolidating each deposited layer by ramming, watering etc, disposing of surplus excavated soil, as directed within a lead of 50 m and lift upto 1.5 m.: All kind of Soil	232.00			EACH	
2	R.C.C. Standards post/ struts/rails/ pales of mix 1:1.5:3 (1 cement : 1.5 coarse sand : 3 graded stone aggregate 12.5 mm nominal size) with wooden plugs or 6mm bar nibs wherever required as per direction of Engineer-in-charge (cost of earth works in excavation, concrete works in foundation to be paid separately)	10.96			CUM	
3	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:3:6.-	32.11			CUM	
4	Fencing with R.C.C. post placed at required distance, embedded in cement concrete blocks, every 15th post, last but one end post and corner post shall be strutted on both sides and end post one side only, provided with horizontal lines and two diagonals of barbed wire weighing 9.38 kg per 100 metres (minimum), between the two posts fitted and fixed with G.I. staples on wooden plugs or G.I. binding wire tied to 6 mm bar nibs fixed while casting the post (cost of R.C.C. posts, struts, earth work and concrete to be paid for separately) :- Payment to be made per metre cost of total length of barbed wire used.: With G.I. barbed wire	5240.00			Meter	
5	Supplying and fixing turn buckles and straining bolts for barbed wire fencing	32.00			EACH SET	
6	White washing with lime to give an even shade : New work (three or more coats)	214.02			Sq Mtr	

Contractor

**Executive Engineer (TD)
Deendayal Port Authority**